



**CERTIFICATION**  
**E-59A**  
**BATCH # 18651**

| PRODUCT | DESCRIPTION     | TYPE   | METHOD | SENSITIVITY | FORM | CLASS | APPROVAL DATE |
|---------|-----------------|--------|--------|-------------|------|-------|---------------|
| E-59A   | Cleaner/Remover | I & II | C      | L2*         | NA   | 2     | 12-Aug-2021   |

We hereby certify that this batch of inspection material when tested following manufacture meets the following:

Certificamos que este lote de material de inspección cumple con los siguientes requisitos cuando es probado despues de la fabricación:

- SAE AMS 2644H and on the Qualified Parts List (test reference: AFWAL/MLS 86-88).
- Flowserve
- Velan PS-008, Rev. 10
- MIL-STD-2132 ¶ 7.1.3
- Honeywell EMS 52309-03
- Boeing BSS 7039, BAC 20-20-02
- ISO/FDIS 3452-2006, EN 571-3\*
- NAVSEA 250-1500-1 ¶ 12.5.1.1.1, Rev 17
- RCC-M code 93, Section V-F, sub-section F6420
- Navsea T9074-AS-GIB-010/271 R/1(2014) ¶ 5.6.2 & ¶ 5.6.2.1
- AMS 2647-F, ASTM E-165/E165-18, ASTM E-1417/E1417M-16
- ASME Boiler & Pressure Vessel Code 2019 Section V, Article 6, appendix II-¶-641 & II-¶-642
- 10 CFR part 21 applies.

PO# \_\_\_\_\_

Is free of all known Ozone depleting substances and mercury contamination and was not made in any mercury bearing equipment. Does not contain polychlorinated biphenyl (PCB), nonylphenol ethoxylates (NPE), or RoHS banned substances.

*Esta libre de todas sustancias degradantes del ozono, de contaminación de mercurio, y no fue fabricado usando equipo conteniendo mercurio. No contiene polychlorinated biphenyl (PCB), nonylphenol ethoxylates (NPE), o RoHS sustancias prohibidas.*

- Shelf life is 5 years from date of batch approval.  
*Vida útil de garantía son 5 años desde la fecha del "approval date".*
- Batch number is on bulk labels or bottom of aerosol cans.  
*Numeros de lote se encuentran en las etiquetas de los botes a granel o en el fondo de los botes de aerosol.*

| QUALITY ASSURANCE TESTS                   | REQUIREMENTS                         | BATCH RESULTS |
|---|--------------------------------------|---------------|
| Appearance: ISO 3452-2:2006(E) ¶ 6.1      | Clean, clear liquid, no fluorescence | Pass          |
| Specific Gravity: ISO 3452-2:2006(E) ¶6.3 | 0.730 - 0.765 @ 50°F / 10°C          | 0.742         |
| Performance: ISO 3452-2:2006(E) ¶ 7.2     | *L2 = (100% 50µ, >75% 30µ)           | Pass          |
| Residue: ASTM D1353-13                    | < 0.005 grams/100 ml                 | 0.000 g/100mL |

**MET-L-CHEK QUALITY ASSURANCE**

**BATCH TESTED BY:**

**DENNIS MASON**  
QC CHEMIST

**BATCH APPROVED BY:**

**JUSTINE FORD**  
PLANT CHEMIST



Met-L-Chek Company, 2910 Harvard Avenue | Cleveland, OH 44105

T: (216) 341-0238 | F: (216) 441-1377

E: [info@met-l-chek.com](mailto:info@met-l-chek.com) W: [www.met-l-chek.com](http://www.met-l-chek.com)