



**CERTIFICATION**  
**MPI-FLUID C2**  
**BATCH # 20851**

| PRODUCT      | DESCRIPTION      | TYPE | METHOD | SENSITIVITY | FORM   | CLASS | APPROVAL DATE |
|--------------|------------------|------|--------|-------------|--------|-------|---------------|
| MPI-FLUID C2 | MPI Bath Vehicle | 1    | Wet    | NA          | Liquid | NA    | 23-Dec-2021   |

We hereby certify that this batch of inspection material when tested following manufacture meets the following:  
Certificamos que este lote de material de inspección cumple con los siguientes requisitos cuando es probado despues de la fabricación:

- ISO-9934-2
- A-A-59230 2 July 1998
- MIL-STD-2132D, 2003
- AMS 2641C-2015, Type I
- Pratt & Whitney PMC 1887
- NAVSEA T9074-AS-GIB-010/271,6/30/97
- ASTM E1444/E1444M-16, ASTM E709-15
- T9074-AS-G1B-010/271 superceedes MIL-STD-271F
- 10CFR Part 21 applies.

PO# \_\_\_\_\_

Is free of all known Ozone depleting substances and mercury contamination and was not made in any mercury bearing equipment. Does not contain polychlorinated biphenyl (PCB), nonylphenol ethoxylates (NPE), or RoHS banned substances.  
*Esta libre de todas sustancias degradantes del ozono, de contaminación de mercurio, y no fue fabricado usando equipo conteniendo mercurio. No contiene polychlorinated biphenyl (PCB), nonylphenol ethoxylates (NPE), o RoHS sustancias prohibidas.*

- Warranty shelf life is 5 years from date of batch approval.  
*Vida útil de garantía son 5 años desde la fecha del "approval date".*
- Batch number is on bulk labels or bottom of aerosol cans.  
*Numeros de lote se encuentran en las etiquetas de los botes a granel o en el fondo de los botes de aerosol.*

| QUALITY ASSURANCE TESTS                                   | REQUIREMENTS                                 | BATCH RESULTS          |
|---|--|------------------------|
| Appearance:   | Clean, clear liquid, free of foreign matter. | PASS                   |
| Fluorescence: ISO-9934-2 ¶ 7.6; AMS2641C ¶3.2.3.2         | No fluorescence                              | PASS                   |
| Flash Point: ASTM D-93                                    | > 93.3°C (> 200°F)                           | 203 °F                 |
| Viscosity: ASTM D-445; ISO-9934-2 ¶ 7.9, AMS-2641C type 1 | < 3.0 mm <sup>2</sup> /s @ 37.7°C (100°F)    | 2.4 mm <sup>2</sup> /s |
| Specific gravity  | 0.7900 - 0.8400 @ 15.5°C(60°F)               | 0.8193                 |

**MET-L-CHEK QUALITY ASSURANCE**

**BATCH TESTED BY:**

**DENNIS MASON**  
QC CHEMIST

**BATCH APPROVED BY:**

**JUSTINE FORD**  
PLANT CHEMIST



Met-L-Chek Company, 2910 Harvard Avenue | Cleveland, OH 44105

T: (216) 441-4900 | F: (216) 441-1377

E: info@met-l-chek.com W: www.met-l-chek.com