

CERTIFICATION

FBP-912

Batch #: 35482

Product	Description	Type	Method	Sensitivity	Form	Class	Approval Date
FBP-912	Fluorescent Penetrant	I	A & C	2	N/A	N/A	20-JUN-24

We hereby certify that this batch of inspection material when tested following manufacture meets the following:

Certificamos que este lote de material de inspección cumple con los siguientes requisitos cuando es probado después de la fabricación:

- SAE AMS 2644H and on the Qualified Products List (test reference: AFRL-RXS 19-049)
- MIL-STD-2132
- Safran PR-5000
- ISO/FDIS 3452-2:2021
- Honeywell EMS 52309, HGS1010
- Rolls-Royce RPS-702-7, RRP 58003 Rev. H
- Boeing BSS 7039, BAC 20-20-02, PSD 6-46, PSD 8-4
- General Electric Aircraft Engines 70-32-02 & Gas Turbines LM6000 PC
- NAVSEA 250-1500-1 ¶ 12.5.1.1.1, Rev 18 & T9074-AS-G1B-010/271 Rev. 1 2014
- AMS 2647G, ASTM E1209-18, ASTM E165/E165M-18, ASTM E1417/E1417M-21
- ASME Boiler & Pressure Vessel Code 2021 Section V, Article 6, appendix II-¶641& II-¶642
- 10CFR part 21 applies

- Shelf life is 5 years from date of batch approval.

Vida útil de garantía son 5 años desde la fecha del "approval date".

- Batch number is on bulk labels or bottom of aerosol cans.

Numeros de lote se encuentran en las etiquetas de los botes a granel o en el fondo de los botes de aerosol.

Is free of all known Ozone depleting substances and mercury contamination and was not made in any mercury bearing equipment. Does not contain polychlorinated biphenyl (PCB), nonylphenol ethoxylates (NPE), or RoHS banned substances.

Esta libre de todas sustancias degradantes del ozono, de contaminación de mercurio, y no fue fabricado usando equipo conteniendo mercurio.

No contiene polychlorinated biphenyl (PCB), nonylphenol ethoxylates (NPE), o RoHS sustancias prohibidas.

TEST DESCRIPTION	UNIT	SPECIFICATION	RESULT
Density	G/L	958.0 - 983.0	981.0
Viscosity: ASTM D445-21; AMS 2644H ¶ 3.3.4	MM2/S	22.9 - 28.0	24.6
Flash Point: ASTM D93-20; AMS 2644H ¶ 3.3.3	C	93.3 Minimum	100.0
Fluorescent Brightness: ASTM E1135-19; AMS 2644H ¶ 3.3.8.3.3	%	80.0 Minimum	119.0
Water Tolerance: AMS 2644H ¶ 3.3.8.5	%	5.0 Minimum	8.3
Water Content: ASTM E1417/E1417M-21, Annex A1 (Karl Fischer)	%	1.00 Maximum	0.46
Sulfur Content: ASTM E165/E165M-23 ¶ 9.1.2, Annex A4	PPM	200 Maximum	13
Chloride Content: ASTM E165/E165M-23 ¶ 9.1.2, Annex A4	PPM	200 Maximum	11
Total Halogen Content: ASTM E165/E165M-23 ¶ 9.1.2, Annex A4	PPM	200 Maximum	30
Appearance	P/F	Clear, yellow green liquid, no sediment	PASS
Performance: ASTM E1417/E1417M-21 ¶ 7.8.3	P/F	Equal to MLC Level 2 Standard	PASS
Removability: AMS 2644H ¶ 3.3.8.6	P/F	Equal to MLC Standard	PASS

This certificate of analysis has been transmitted electronically and is valid without a signature