

CERTIFICATION

E-57

Batch #: 50067



Product	Description	Type	Method	Sensitivity	Form	Class	Approval Date
E-57	Lipophilic Emulsifier	1	B	N/A	N/A	N/A	18-SEP-26

We hereby certify that this batch of inspection material when tested following manufacture meets the following:

Certificamos que este lote de material de inspección cumple con los siguientes requisitos cuando es probado despues de la fabricación:

-SAE AMS 2644J and on the Qualified Products List (test reference: AFWAL/MLS 86-88, AFRL/MLS 98-165)

- MIL-STD-2132

- ISO/FDIS 3452-2:2021

- Safran Aircraft Engines Pr-5000, Issue F, §§6.4.1 and 6.4.2

- Honeywell EMS 52309, HGS1010

- Pratt & Whitney FPM PMC 4355-7 Rev. AV, dated 01/16/2026

- Rolls-Royce RRP 58003 Rev. K

- Boeing BSS 7039, BAC 20-20-02, PSD 6-46, PSD 8-4

- AMS 2647G, ASTM E165/E165M-23, ASTM E1417/E1417M-21

- General Electric Aircraft Engines 70-32-02, dated 11/22/2023, and General Electric Gas Turbines LM6000

PC

- NAVSEA 250-1500-1, Rev. 19, ¶¶ 12.5.1.1 and 12.5.1.1.1 & T9074-AS-G1B-010/271 Rev. 1 2014

- ASME Boiler and Pressure Vessel Code, 2025 Edition, Section V, Article 6, Mandatory Appendix II, ¶¶

II-641 and II-642

- 10CFR part 21 applies

• Shelf life is 5 years from date of batch approval.

Vida útil de garantía son 5 años desde la fecha del "approval date".

• Batch number is on bulk labels or bottom of aerosol cans.

Numeros de lote se encuentran en las etiquetas de los botes a granel o en el fondo de los botes de aerosol.

Is free of all known Ozone depleting substances and mercury contamination and was not made in any mercury bearing equipment. Does not contain polychlorinated biphenyl (PCB), nonylphenol ethoxylates (NPE), or RoHS banned substances.

Esta libre de todas sustancias degradantes del ozono, de contaminación de mercurio, y no fue fabricado usando equipo conteniendo mercurio.

No contiene polychlorinated biphenyl (PCB), nonylphenol ethoxylates (NPE), o RoHS sustancias prohibidas.

TEST DESCRIPTION

Density: ISO 3452-2:2021 ¶ 6.3

Viscosity: ASTM D445-21; AMS 2644J ¶ 3.3.4; ISO 3452-2:2021 ¶ 6.4

Flash Point: ASTM D93-20; AMS 2644J ¶ 3.3.3; ISO 3452-2:2021 ¶ 6.5

Water Tolerance: ISO 3452-2:2021 ¶ 6.10

Sulfur Content: ASTM E165/E165M-23 ¶ 9.1.2, Annex A4

Chloride Content: ASTM E165/E165M-23 ¶ 9.1.2, Annex A4

Total Halogen Content: ASTM E165/E165M-23 ¶ 9.1.2, Annex A4

Water Content: ASTM E1417/E1417M-21, Annex A1 (Karl Fischer)

Appearance

Performance: AMS 2644J ¶ 3.3.8.6; ISO 3452-2:2021 ¶ 6.2

UNIT

G/L

MM2/S

C

%

PPM

PPM

PPM

%

P/F

P/F

SPECIFICATION

817.2 - 998.8

27.0 - 34.4

93.3 Minimum

5.0 Minimum

200 Maximum

200 Maximum

200 Maximum

5.00 Maximum

Clear, pink liquid, no sediment

Equal to MLC Standard

RESULT

911.6

29.6

105.0

5.7

45

9

17

3.60

PASS

PASS

This certificate of analysis has been transmitted electronically and is valid without a signature

