

CERTIFICATION



E-59A

Batch #: 50501

Product	Description	Type	Method	Sensitivity	Form	Class	Approval Date
E-59A	Cleaner/Remover	I & II	C	L2*	NA	2	06-OCT-26

We hereby certify that this batch of inspection material when tested following manufacture meets the following:

Certificamos que este lote de material de inspección cumple con los siguientes requisitos cuando es probado despues de la fabricación:

- SAE AMS-2644J and on the Qualified Products List(test reference: AFWAL/MLS 86-88)
- MIL-STD-271
- Safran Aircraft Engines Pr-5000, Issue F, §§6.4.1 and 6.4.2
- Velan PS-008, Rev. 10
- MIL-STD-2132 ¶ 7.1.3
- ISO/FDIS 3452-2:2021
- Honeywell HGS1010, EMS 52309
- RCC-M code 93, Section V-F, sub-section F6420
- Rolls-Royce RRP 58003 Rev. K
- Navsea T9074-AS-GIB-010/271 R/1(2014) ¶ 5.6.2 & ¶ 5.6.2.1
- Boeing BSS 7039, BAC 20-20-02, BAC 5423, PSD 6-46, PSD 8-4
- General Electric Aircraft Engines 70-32-02, dated 11/22/2023, and General Electric Gas Turbines LM6000

PC

- NAVSEA 250-1500-1, Rev. 19, ¶¶ 12.5.1.1 and 12.5.1.1.1 & T9074-AS-G1B-010/271 Rev. 1 2014
- AMS 2647G, ASTM E165M-23, ASTM E1417M-21, ASTM E-1418M-21, ASTM E1209-18
- ASME Boiler and Pressure Vessel Code, 2025 Edition, Section V, Article 6, Mandatory Appendix II, ¶¶ II-641 and II-642

- 10CFR Part 21 applies

- Shelf life is 5 years from date of batch approval.

Vida útil de garantía son 5 años desde la fecha del "approval date".

- Batch number is on bulk labels or bottom of aerosol cans.

Numeros de lote se encuentran en las etiquetas de los botes a granel o en el fondo de los botes de aerosol.

Is free of all known Ozone depleting substances and mercury contamination and was not made in any mercury bearing equipment. Does not contain polychlorinated biphenyl (PCB), nonylphenol ethoxylates (NPE), or RoHS banned substances.

Esta libre de todas sustancias degradantes del ozono, de contaminación de mercurio, y no fue fabricado usando equipo conteniendo mercurio. No contiene polychlorinated biphenyl (PCB), nonylphenol ethoxylates (NPE), o RoHS sustancias prohibidas.

TEST DESCRIPTION

Specific Gravity: ISO 3452-2:2021 ¶ 6.3

Performance Level 2 (50 micron): ISO 3452-2:2021 ¶ 6.2

Performance Level 2 (30 micron): ISO 3452-2:2021 ¶ 6.2

Residue: ASTM D1353-13

Appearance: ISO 3452-2:2021 ¶ 6.1

UNIT

P/F

%

%

G/100ML

P/F

SPECIFICATION

0.730 - 0.765

100 Minimum

75 Minimum

0.005 Maximum

Clear liquid, no fluorescence

RESULT

0.739

100

90

0.000

PASS

This certificate of analysis has been transmitted electronically and is valid without a signature

