McGean
2910 Harvard Ave
Cleveland, OH 44105-1377
Tel: 216-441-4900
Fax: 216-441-4544
www.mcgean.com

CERTIFICATION

R-504

Batch #: 50668

Product	Description	Type	Method	Sensitivity	Form	Class	Approval Date
R-504	Cleaner/Remover	I & II	N/A	L2*	N/A	2	16-OCT-26

We hereby certify that this batch of inspection material when tested following manufacture meets the following:
Certificamos que este lote de material de inspeccíon cumple con los siguientes requisitos cuando es probado despues de la fabricación:

- SAE AMS-2644J and on the Qualified Products List(test reference: AFWAL/MLS 86-88)
- MIL-STD-271
- Safran Aircraft Engines Pr-5000, Issue F, §§6.4.1 and 6.4.2
- Velan PS-008, Rev. 10
- MIL-STD-2132 ¶ 7.1.3
- ISO/FDIS 3452-2:2021
- Honeywell HGS1010, EMS 52309
- Pratt & Whitney FPM PMC #9008-AJ
- Rolls-Royce RRP 58003 Rev. K
- RCC-M code 93, Section V-F, sub-section F6420
- Navsea T9074-AS-GIB-010/271 R/1(2014) ¶ 5.6.2 & ¶ 5.6.2.1
- Boeing BSS 7039, BAC 20-20-02, BAC 5423, PSD 6-46, PSD 8-4
- General Electric Aircraft Engines 70-32-02, dated 11/22/2023, and General Electric Gas Turbines LM6000 PC
- NAVSEA 250-1500-1, Rev. 19, ¶¶ 12.5.1.1 and 12.5.1.1.1 & T9074-AS-G1B-010/271 Rev. 1 2014
- AMS 2647G, ASTM E165M-23, ASTM E1417M-21, ASTM E-1418M-21, ASTM E1209-18
- ASME Boiler and Pressure Vessel Code, 2025 Edition, Section V, Article 6, Mandatory Appendix II, ¶¶ II-641 and II-642
- 10CFR part 21 applies.

• Shelf life is 5 years from date of batch approval.
Vida útil de garantia son 5 años desde la fecha del "approval date".
• Batch number is on bulk labels or bottom of aerosol cans.
Numeros de lote se encuentran en las etiquetas de los botes a granel o en el fondo de los botes de aerosol.

Is free of all known Ozone depleting substances and mercury contamination and was not made in any mercury bearing equipment. Does notcontain polychlorinated biphenyl (PCB), nonylphenol ethoxylates (NPE), or RoHS banned substances.
Esta libre de todas sustancias degradantes del ozono, de contaminación de mercurio, y no fue fabricado usando equipo conteniendomercurio. No contiene polychlorinated biphenyl (PCB), nonylphenol ethoxylates (NPE), o RoHS sustancias prohibidas.

TEST DESCRIPTION	UNIT	SPECIFICATION	RESULT
Specific Gravity: PMC 9008; ISO 3452-2:2021 ¶ 6.3	P/F	0.791 - 0.793	0.793
Performance Level 2 (50 micron): ISO 3452-2:2021 ¶ 6.2	%	100 Minimum	100
Performance Level 2 (30 micron): ISO 3452-2:2021 ¶ 6.2	%	75 Minimum	90
Residue: ISO 3452-2:2021 ¶ 6.13.1.1; ASME B&PVC	G/100ML	0.005 Maximum	0.004
Phenol Content: PMC 9008	PPM	5 Maximum	0
Appearance: ISO 3452-2:2021 ¶ 6.1	P/F	Clear liquid, no flourescence	PASS

This certificate of analysis has been transmitted electronically and is valid without a signature