McGean
2910 Harvard Ave
Cleveland, OH 44105-1377
Tel: 216-441-4900
Fax: 216-441-4544
www.mcgean.com

# CERTIFICATION

## FBP-913

## Batch #: 50827

| Product | Description | Type | Method | Sensitivity | Form | Class | Approval Date |
|---|---|---|---|---|---|---|---|
| FBP-913 | Fluorescent Penetrant | 1 | A & C | 3 | NA | NA | 02-NOV-26 |

We hereby certify that this batch of inspection material when tested following manufacture meets the following:
Certificamos que este lote de material de inspeccíon cumple con los siguientes requisitos cuando es probado despues de la fabricación:

-SAE AMS 2644J and on the Qualified Products List (test reference: AFRL-RXS 19-049)
- MIL-STD-2132
- Safran Aircraft Engines Pr-5000, Issue F, §§6.4.1 and 6.4.2
- ISO/FDIS 3452-2:2021
- Honeywell EMS 52309, HGS1010
- Rolls-Royce RRP 58003 Rev. K
- Boeing BSS 7039, BAC 20-20-02, PSD 6-46, PSD 8-4
- General Electric Aircraft Engines 70-32-02, dated 11/22/2023, and General Electric Gas Turbines LM6000 PC
- NAVSEA 250-1500-1, Rev. 19, ¶¶ 12.5.1.1 and 12.5.1.1.1 & T9074-AS-G1B-010/271 Rev. 1 2014
- AMS 2647G, ASTM E1209-18, ASTM E165/E165M-23, ASTM E1417/E1417M-21
- ASME Boiler and Pressure Vessel Code, 2025 Edition, Section V, Article 6, Mandatory Appendix II, ¶¶ II-641 and II-642
- 10CFR part 21 applies
- Pratt & Whitney FPM PMC #4360-12 Rev. AH, dated 04/08/2024

• Shelf life is 5 years from date of batch approval.
Vida útil de garantia son 5 años desde la fecha del "approval date".
• Batch number is on bulk labels or bottom of aerosol cans.
Numeros de lote se encuentran en las etiquetas de los botes a granel o en el fondo de los botes de aerosol.

Is free of all known Ozone depleting substances and mercury contamination and was not made in any mercury bearing equipment. Does not containpolychlorinated biphenyl (PCB), nonylphenol ethoxylates (NPE), or RoHS banned substances.
Esta libre de todas sustancias degradantes del ozono, de contaminación de mercurio, y no fue fabricado usando equipo conteniendo mercurio. Nocontiene polychlorinated biphenyl (PCB), nonylphenol ethoxylates (NPE), o RoHS sustancias prohibidas.

| TEST DESCRIPTION | UNIT | SPECIFICATION | RESULT |
|---|---|---|---|
| Density | G/L | 958.0 - 998.0 | 980.2 |
| Viscosity: ASTM D445-21; AMS 2644J ¶ 3.3.4; PMC 4360-12 Rev AH | MM2/S | 23.7 - 29.0 | 26.0 |
| Flash Point: ASTM D93-20; AMS 2644J ¶ 3.3.3; PMC 4360-12 Rev AH | C | 93.3 Minimum | 111.0 |
| Fluorescent Brightness: ASTM E1135-19; AMS 2644J ¶ 3.3.8.3.3 | % | 90.0 Minimum | 113.4 |
| Water Tolerance: AMS 2644J ¶ 3.3.8.5 | % | 5.0 Minimum | 23.1 |
| Water Content: ASTM E1417/E1417M-21, Annex A1 (Karl Fischer) | % | 1.00 Maximum | 0.56 |
| Sulfur Content: ASTM E165/E165M-23 ¶ 9.1.2, Annex A4 | PPM | 200 Maximum | 14 |
| Chloride Content: ASTM E165/E165M-23 ¶ 9.1.2, Annex A4 | PPM | 200 Maximum | 13 |
| Total Halogen Content: ASTM E165/E165M-23 ¶ 9.1.2, Annex A4 | PPM | 200 Maximum | 26 |
| Appearance: PMC 4360-12 Rev AH | P/F | Clear, yellow green liquid, no sediment | PASS |
| Performance: ASTM E1417/E1417M-21 ¶ 7.8.3 | P/F | Equal to MLC Level 3 Standard | PASS |
| Removability: AMS 2644J ¶ 3.3.8.7 | P/F | Equal to MLC Standard | PASS |

**This certificate of analysis has been transmitted electronically and is valid without a signature**